

# Exceptions

- Exceptions
- Throwing Exceptions
- Handling Exceptions
- Try statement and catch / finally clauses
- Checked and unchecked exceptions
- Throws clause
- Reading for this lecture: L&L 10.1 – 10.6

# Exceptions

- An *exception* is an object that flags/ describes the occurrence of an unusual or erroneous situation
- Java has a predefined set of Exception classes for errors that can occur during execution
  - e.g ArithmeticException
- We can write our own Exception classes if needed
- When code in a program detects an “impossible condition”, it can *throw* a defined exception object
- The manner in which exceptions are processed is an important design consideration

# Throwing Exceptions

- For code to “throw” an exception:
  - It must detect the “impossible” situation
  - Instantiate and “throw” an exception object
- **Example (throw is a Java reserved word):**

```
if (boolean logic to detect impossible situation)
    throw new NameOfException("text to print");
```
- Some Java statements or methods in the class library may throw exceptions this way

# Handling Exceptions

- A program can deal with an exception in one of three ways:
  - ignore it (Let the JVM shut down the program)
  - handle it where it occurs
  - handle it at another place in the program
- If we ignore it, we get something like this in the interactions pane (See Zero.java):

```
java.lang.ArithmeticException: / by zero
  at Zero.main(Zero.java:17)
  at sun.reflect.NativeMethodAccessor...
```

...

# The `try` Statement / `catch` Clause

- To handle an exception in a program, the line that may throw the exception is executed within a `try` statement followed by one or more `catch` clauses
- Each `catch` clause has an exception type and reference name and is called an *exception handler*
- If an exception occurs,
  - Processing stops in the body of the `try` statement
  - Processing continues at the start of the first `catch` clause matching the type of exception that occurred
- The reference name can be used in the `catch` clause to get information about the exception

# The `finally` Clause

- A try statement can have an optional clause following the catch clauses, designated by the reserved word `finally`
- The Java statements in the `finally` clause are always executed
  - If no exception is generated, the statements in the `finally` clause are executed after the statements in the try block complete
  - If an exception is generated, the statements in the `finally` clause are executed after the statements in the appropriate catch clause complete

# Example of try-catch-finally

```
try
{
    System.out.println(Integer.parseInt(string));
}
catch (NumberFormatException e)
{
    System.out.println("Caught exception: " + e);
}
finally
{
    System.out.println("Done.");
}
```

# Exception Propagation

- An exception can be propagated up to the caller to be handled at a higher level if it is not appropriate to handle it where it occurs
- Exceptions *propagate* up through the method calling hierarchy until they are caught and handled or until they reach the level of the `main` method and/or JVM
- See `Propagation.java` (page 546)
- See `ExceptionScope.java` (page 547)



# Checked/Unchecked Exceptions

- An exception is considered to be either *checked* or *unchecked*
- A `RuntimeException` or its decendents such as `ArithmeticException`, `NullPointerException`, etc are the only ones considered to be *unchecked*
- All other exceptions are considered to be *checked*
- Many of the checked exceptions are related to input / output, e.g. `IOException`

# Checked Exceptions

- If a method can generate a checked exception, it must have a `throws` clause in its header
- (Note: “`throws`” is a different reserved word)
- If `method1` calls `method2` that has a `throws` clause in its method header, `method1` must:
  - Use `try-catch` around the call to `method2`
  - OR
  - Have a `throws` clause in its own method header
- The compiler will issue an error if a checked exception is not caught or listed in a `throws` clause

# Example of the `throws` clause

```
public class FileDisplay
{
    public FileDisplay() throws IOException
    {
        Scanner scan = new Scanner(System.in);
        System.out.println("Enter name of file");
        File file = new File(scan.nextLine());

        // this line may throw an IOException
        // and its not inside a try statement
        scan = new Scanner (file);
    }
}
```

# Unchecked Exceptions

- An unchecked exception does not require explicit handling
- Code or calls to a method that may generate an unchecked exception can be put inside a `try-catch` statement, but that is optional