


UMass Boston Computer Science  
**CS450 High Level Languages** (section 2)

# Intertwined Data


Wednesday, October 30, 2024



THE GOVERNMENT FINALLY  
DECIDES TO PUT AN END  
TO ALL THE ARGUMENTS.

## *Logistics*

- HW 8 out
  - due: Mon 11/4 12pm (noon) EST
- (Daylight Savings ends 11/3)
- **no lecture**: Veteran's Day Mon 11/11



THE GOVERNMENT FINALLY  
DECIDES TO PUT AN END  
TO ALL THE ARGUMENTS.

# Intertwined Data Definitions

- Come up with a **Data Definition** for ...
- ... valid Racket Programs

# Valid Racket Programs

- 1
- “one”
- (+ 1 2)

```
;; A RacketProg is a:
```

```
;; - Number
```

```
;; - String
```

```
;; - ???
```

# Valid Racket Programs

- 1
- “one”
- (+ 1 2)

```
;; A RacketProg is a:  
;; - Atom
```

```
;; - ???
```

```
;; An Atom is a:  
;; - Number  
;; - String
```

# Valid Racket Programs

• (+ 1 2) ← List of ... atoms?

“symbol”

```
;; A RacketProg is a:  
;; - Atom  
;; - List<Atom> ???
```

```
;; An Atom is a:  
;; - Number  
;; - String  
;; - Symbol
```

Written with a single quote, e.g., '+

# Valid Racket Programs

- `(* (+ 1 2) (- 4 3))`

Tree?

- `(* (+ 1 2) (- 4 3) (/ 10 5))`

Each tree “node” is a list, of ... RacketProgs ??

But: how many values does each node have??

```
;; A RacketProg is a:  
;; - Atom  
;; - List<???  
;; - Tree<???
```

```
;; An Atom is a:  
;; - Number  
;; - String  
;; - Symbol
```

# Valid Racket Programs

- `(* (+ 1 2) (- 4 3))`

Tree?

- `(* (+ 1 2) (- 4 3) (/ 10 5))`

Each tree "node" is a list, of ... RacketProgs ??

But: how many values does each node have??

```
;; A RacketProg is a:  
;; - Atom  
;; - ProgTree
```

```
;; An Atom is a:  
;; - Number  
;; - String  
;; - Symbol
```

```
;; A ProgTree is one of:  
;; - empty  
;; - (cons RacketProg ProgTree)
```

Recursive Data Def!



# Valid Racket Programs

Also, **Intertwined Data Defs!**

```
;; A RacketProg is a:  
;; - Atom  
;; - ProgTree
```

```
;; A ProgTree is one of:  
;; - empty  
;; - (cons RacketProg ProgTree)
```

```
;; An Atom is one of:  
;; - Number  
;; - String  
;; - Symbol
```

# Intertwined Data

- A set of Data Definitions that reference each other
- Templates should be defined together ...

```
;; A RacketProg is a:  
;; - Atom  
;; - ProgTree
```

```
;; A ProgTree is one of:  
;; - empty  
;; - (cons RacketProg ProgTree)
```

```
;; An Atom is one of:  
;; - Number  
;; - String  
;; - Symbol
```

# Intertwined Data

- A set of Data Definitions that reference each other
- Templates should be defined together ...
  - ... and should reference each other's templates (when needed)

```
;; A RacketProg is one of:  
;; - Atom  
;; - ProgTree
```

```
(define (prog-fn p) ...)
```

```
;; A ProgTree is one of:  
;; - empty  
;; - (cons RacketProg ProgTree)
```

```
(define (ptree-fn t) ...)
```

```
;; An Atom is one of:  
;; - Number  
;; - String  
;; - Symbol
```

```
(define (atom-fn a) ...)
```

???

- [File: lecture16.rkt](#)
- [Submit: ... to GradeScope later](#)

# In-class Coding 10/30 #1: Intertwined Templates

- Templates should be defined together ...
  - ... and should reference each other's templates (when needed)

```
;; A RacketProg is one of:  
;; - Atom  
;; - ProgTree
```

```
(define (prog-fn p) ...)
```

```
;; A ProgTree is one of:  
;; - empty  
;; - (cons RacketPRog ProgTree)
```

```
(define (ptree-fn t) ...)
```

```
;; An Atom is one of:  
;; - Number  
;; - String  
;; - Symbol
```

```
(define (atom-fn a) ...)
```

???

# Intertwined Templates

```
;; A RacketProg is one of:  
;; - Atom  
;; - ProgTree
```

```
(define (prog-fn s)  
  (cond  
    [(atom? s) ... (atom-fn s) ...]  
    [else ... (ptree-fn s) ...]))
```

```
;; A ProgTree is one of:  
;; - empty  
;; - (cons RacketProg ProgTree)
```

```
(define (ptree-fn t)  
  (cond  
    [(empty? t) ...]  
    [else ... (prog-fn (first t)) ... (ptree-fn (rest t)) ...]))
```

```
;; An Atom is one of:  
;; - Number  
;; - String  
;; - Symbol
```

```
(define (atom-fn a)  
  (cond  
    [(number? a) ... ]  
    [(string? a) ... ]  
    [else ... ]))
```

**Intertwined data have  
intertwined templates!**

# A “Racket Prog” = S-expression!

```
;; A RacketProg Sexpr is one of:  
;; - Atom  
;; - ProgTree
```

```
(define (sexpr-fn s)  
  (cond  
    [(atom? s) ... (atom-fn s) ...]  
    [else ... (ptree-fn s) ...]))
```

```
;; A ProgTree is one of:  
;; - empty  
;; - (cons RacketProg Sexpr ProgTree)
```

```
(define (ptree-fn t)  
  (cond  
    [(empty? t) ...]  
    [else ... (sexpr-fn (first t)) ... (ptree-fn (rest t)) ...]))
```

```
;; An Atom is one of:  
;; - Number  
;; - String  
;; - Symbol
```

```
(define (atom-fn a)  
  (cond  
    [(number? a) ... ]  
    [(string? a) ... ]  
    [else ... ]))
```

- [File: lecture16.rkt](#)
- [Submit: GradeScope "in-class 10/30"](#)

# In-class Coding 10/30 #2: Counting Symbols

```
;; A Sexpr is one of:  
;; - Atom  
;; - ProgTree
```

```
;; An Atom is one of:  
;; - Number  
;; - String  
;; - Symbol
```

```
;; count : Symbol Sexpr -> Nat  
;; Computes the number of times the given  
;; symbol appears in the given s-expression
```

```
;; A ProgTree is one of:  
;; - empty  
;; - (cons Sexpr ProgTree)
```

```
;; count-atom : Symbol Atom -> Nat  
;; ???
```

```
;; count-ptree : Symbol ProgTree -> Nat  
;; ???
```

