

UMass Boston Computer Science
CS450 High Level Languages

Implementing Function Calls

Thursday, April 22, 2025

Logistics

- HW 10 in
 - ~~due: Tues 4/22 11am EST~~
- HW 11 out
 - due: Tues 4/29 11am EST


The “CS450” Programming Lang!

Programmer writes:



```
;; A Program is one of:  
;; - Atom  
;; - `(+ ,Program ,Program)  
;; - `(* ,Program ,Program)  
;; - `(~= ,Program ,Program)  
;; - `(iffy ,Program ,Program ,Program)
```

Adding Variables



Design Recipe For Accumulator Functions

When a function needs “extra information”:

1. ***Specify accumulator:***

- Name
- Signature
- Invariant

2. ***Define internal “helper” fn with extra accumulator arg***

(Helper fn does not need extra description, statement, or examples, if they are the same ...)

3. ***Call “helper” fn , with initial accumulator value, from original fn***

run, with an accumulator

```
;; run: AST -> Result
;; Computes result of running a CS450 Lang program AST

(define (run p)
  ;; accumulator acc : Environment
  ;; invariant: Contains variable values ... currently in-scope
  (define (run/acc p acc)
    (match p
      [(num n) n]
      [(add x y) (+ (run/acc x) (run/acc y))])
  (run/acc p ???))
```

Environments

- A data structure that “associates” two things (var, val) together
 - E.g., maps, hashes, list-of-pairs

```
;; An Environment is one of:  
;; - empty  
;; - (cons (list Var Result) Environment)  
  
;; interpretation: a runtime environment for  
;; (i.e., gives meaning to) cs450-lang variables  
  
;; if there are duplicates,  
;; vars at front of list shadow those in back
```

Environments

- A data structure that “associates” two things (var, val) together
 - E.g., maps, hashes, list-of-pairs

```
;; An Environment is one of:  
;; - empty  
;; - (cons (list Var Result) Environment)
```

- Needed operations:
 - env-add : Env Var Result -> Env
 - env-lookup : Env Var -> Result

Environments

```
;; An Environment is one of:  
;; - empty  
;; - (cons (list Var Result) Environment)
```

- Needed operations:

- env-add : Env Var Result -> Env
- env-lookup : Env Var -> Result

;; interpretation: a runtime environment
;; gives meaning to cs450lang variables

;; for duplicates, vars at front of
;; list shadow those in back

Think about examples where this happens!

env-add examples

;; An Environment (Env) is one of:
;; - empty
;; - (cons (list Var Result) Env)

;; env-add: Env Var Result -> Env

```
(check-equal? (env-add '() 'x 1)
  '((x 1))) ; add to empty
```

```
(check-equal? (env-add '((x 1)) 'y 2)
  '((y 2) (x 1))) ; add new var
```

```
(check-equal? (env-add '((x 1)) 'x 3)
  '((x 3) (x 1))) ; add shadowed var
```

;; for duplicates, vars at front of
;; list shadow those in back

Env template

2 cases

;; An Environment (Env) is one of:
;; - empty
;; - (cons (list Var Result) Env)

2 cases

```
(define (env-fn env ... )  
  (cond  
    [(empty? env) ... ]  
    [else  
      (match-let  
        ([[(cons (list x result) rest-env) env]])  
        ... x ... result ... (env-fn rest-env ... ) ... ])]))
```

2nd case extracts
components of
compound data

Env template

```
;; An Environment (Env) is one of:  
;; - empty  
;; - (cons (list Var Result) Env)
```

```
(define (env-fn env ... )  
  (cond  
    [(empty? env) ... ]  
    [else  
      (match-let  
        ([ Quasiquote pattern  
          ([( cons pattern  
            ([( cons (list x result) rest-env) env)])  
            ([( `((,x ,result) . ,rest-env) env)])  
            ... x ... result ... (env-fn rest-env ... ) ... ]))
```

The diagram illustrates the matching of a quasiquote pattern against an environment. A green box labeled "Quasiquote pattern" contains the code `(Quasiquote pattern)` followed by a list of three expressions: `(cons (list x result) rest-env)`, `(`, and `(env-fn rest-env ...)`. A blue box labeled "cons pattern" contains the code `(cons (list Var Result) Env)`. A line connects the two boxes, indicating that the quasiquote pattern is being matched against the cons pattern.

```
;; An Environment (Env) is one of:  
;; - empty  
;; - (cons (list Var Result) Env)
```

```
;; env-add: Env Var Result -> Env
```

```
(define (env-add env new-x new-res)  
  (cond  
    [(empty? env) ... ]  
    [else  
     (match-let  
       ([((cons (list x result) rest-env) env)]  
        [(`((,x ,result) . ,rest-env) env)])  
      ... x ... result ... (env-add rest-env ... ) ... )]))
```

Start with template

```
;; An Environment (Env) is one of:  
;; - empty  
;; - (cons (list Var Result) Env)
```

```
;; env-add: Env Var Result -> Env
```

```
(define (env-add env new-x new-res)  
  (cond  
    [(empty? env) ...]  
    [else ...]))
```

Examples

```
(check-equal? (env-add '() 'x 1)  
              '((x 1)) ); add to empty
```

Base case – empty env

```
;; An Environment (Env) is one of:  
;; - empty  
;; - (cons (list Var Result) Env)
```

```
;; env-add: Env Var Result -> Env
```

```
(define (env-add env new-x new-res)  
  (cond  
    [(empty? env) (cons (list new-x new-res) env)]  
    [else ...]))
```

Base case – empty env

```
;; An Environment (Env) is one of:  
;; - empty  
;; - (cons (list Var Result) Env)
```

```
;; env-add: Env Var Result -> Env
```

```
(define (env-add env new-x new-res)  
  (cond  
    [(empty? env) (cons (list new-x new-res) env)]  
    [else ...]))
```

recursive case?
(non-empty env)

Examples

```
(check-equal? (env-add '((x 1)) 'y 2)  
  '((y 2) (x 1))) ; add new var
```

```
(check-equal? (env-add '((x 1)) 'x 3)  
  '((x 3) (x 1))) ; add shadowed var
```

```
;; An Environment (Env) is one of:  
;; - empty  
;; - (cons (list Var Result) Env)
```

```
;; env-add: Env Var Result -> Env
```

```
(define (env-add env new-x new-res)  
  (cond  
    [(empty? env) (cons (list new-x new-res) env)]  
    [else (cons (list new-x new-res) env)]))
```

recursive case?
(non-empty env)

Sometimes you start with template ... but don't use all the pieces!

```
;; An Environment (Env) is one of:  
;; - empty  
;; - (cons (list Var Result) Env)
```

```
;; env-add: Env Var Result -> Env
```

```
(define (env-add env new-x new-res)  
  (cons (list new-x new-res) env))
```

Collapse similar cases

env-lookup examples

```
;; env-lookup: Env Var -> Result
```

```
(check-equal? (env-lookup '((y 2) (x 1)) 'x)  
    11 ; no dup
```

```
(check-equal? (env-lookup '((x 2) (x 1)) 'x)  
    22 ; duplicate
```

```
(check-equal? (env-lookup '() 'x)  
    UNDEFINED-ERROR ) ; not found!
```

```
;; A Result is one of:  
;; - Number  
;; ...  
;; - UNDEFINED-ERROR
```

An “error” is a valid program “Result”!

... for now, just represent with special Result value

NOTE: we don’t want Racket exception because this is a “CS450 Lang error” ... Racket program runs fine!

env-lookup

```
;; env-lookup: Env Var -> Result
```

```
(define (env-lookup env target-x)
  (cond
    [(empty? env) ...]
    [else
      (match-let
        ([`((,x ,res) . ,rest-env) env])
        ... x ... res ... (env-lookup rest-env ... ) ... )]))
```

TEMPLATE!

env-lookup: empty (error) case

```
;; env-lookup: Env Var -> Result
(define (env-lookup env target-x)
  (cond
    [(empty? env) UNDEFINED-ERROR]
    [else
     ... ]))
```

env-lookup: non-empty case

```
;; env-lookup: Env Var -> Result
(define (env-lookup env target-x)
  (cond
    [(empty? env) UNDEFINED-ERROR]
    [else
      (match-let
        ([`((,x ,res) . ,rest-env) env])
        ... x ... res ... (env-lookup rest-env ... ) ... )]))
```

Extract the pieces

env-lookup: non-empty case

```
;; env-lookup: Env Var -> Result
(define (env-lookup env target-x)
  (cond
    [(empty? env) UNDEFINED-ERROR]
    [else
      (match-let
        ([`((,x,res). ,rest-env) env])
        (if (var=? x target-x)
            res
            ... (env-lookup rest-env ... ) ... ))]))
```

Found target-x

x

env-lookup: non-empty case

```
;; env-lookup: Env Var -> Result
```

```
(define (env-lookup env target-x)
  (cond
    [(empty? env) UNDEFINED-ERROR]
    [else
      (match-let
        ([`((,x ,res) . ,rest-env) env])
        (if (var=? x target-x)
            res
            (env-lookup rest-env target-x)))]))
```

Else, recursive call with remaining env

run, with an Environment accumulator

```
;; run: AST -> Result
(define (run p)
  ;; accumulator env : Environment
  ;; invariant: contains in-scope var + results
  (define (run/env p env)
    (match p
      [(num n) n]
      [(add x y) (+ (run/env x) (run/env y))]))
  (run/env p ??? ))
```

run, with an Environment accumulator

```
;; run: AST -> Result
```

```
(define (run p)
  ;; accumulator env : Environment
  ;; invariant: contains in-scope var + results
  (define (run/env p env)
    (match p
      ...
      [ (vari x) (env-lookup env x) ]
      [ (bind x e body) ... (env-add env x (run/env e env)) ... ]
      ...
    )
  (run/env p ??? ))
```

Don't
name
this var

run, with an Environment accumulator

TODO:

- When are variables “added” to environment???
- What is initial environment?

```
;; run: AST -> Result
```

```
(define (run p)
  ;; accumulator env : Environment
  ;; invariant: contains in-scope var + results
  (define (run/env p env)
    (match p
      ...
      [(vari x) (env-lookup env x)]
      [(bind ???
        body) ... (env-add env x ???
          e env) ...]
      ...
      )))
  (run/env p ??? ))
```

Programs that Add Variables to Environment

```
;; A Program is one of:  
;; - Atom  
;; - Variable (Var)  
;; - ?????
```

Programs that Add Variables to Environment


```
;; A Program is one of:  
;; - Atom  
;; - Variable (Var)  
;; - `(bind [,Var ,Program] ,Program)  
;; - ...  
;; (like "let" in other langs)
```

Programs that Add Variables to Environment

```
;; A Program is one of:  
;; - Atom  
;; - Variable (Var)  
;; - `(bind [,Var ,Program] ,Program)  
;; - ...
```

Need to be more careful parsing

Valid
Program?



```
;; An AST is one of:  
;; - ...  
;; - (mk-var Symbol)  
;; - (mk-bind Symbol AST AST)  
;; - ...  
  
;; ...  
(struct vari [name])  
(struct bind [var expr body])  
;; ...
```

‘(bind)

‘(bind [])

‘(bind [1 2] 3)

Interlude: Racket exceptions

Exceptions are just special structs

Super struct (enables using exception API)

```
(struct exn:fail:syntax:cs450 exn:fail:syntax [])
```

```
(define/contract (parse p)
  (-> Program? AST?))
  (match p
    [(? atom?) (parse-atom p)]
    ...
    [`(,fn . ,args) ... ]
    [_ (error ... )]))
```

Interlude: Racket exceptions

Exceptions are just special structs

Super struct (enables using exception API)

```
(struct exn:fail:syntax:cs450 exn:fail:syntax [])
```

```
(define/contract (parse p)
  (-> Program? AST?))
  (match p
    [(? atom?) (parse-atom p)]
    ...
    [(`(,fn . ,args) ... ]
    [_ (raise-syntax-error
        'parse "not a valid CS450 Lang program" p
        #:exn exn:fail:syntax:cs450)]))
```

```
(define/contract (parse p)
  (-> Program? AST?))
  (match p
    ...
    [ `(` bind [, (and (? symbol?) x) , e] , bod) ... ]
    ...
    [ `(` , fn . , args) ... ]
    [_ (raise-syntax-error
        'parse "not a valid CS450 Lang program" p
        #:exn exn:fail:syntax:cs450))])
```

```
(define/contract (parse p)
  (-> Program? AST?))
  (match p
    ...
    [`(bind [, (and (? symbol?) x) ,e] ,bod) ... ]
    [`(bind . _)
      (raise-syntax-error 'parse "invalid bind syntax" p
        #:exn exn:fail:syntax:cs450)]
      Bind parse error case
    [`,fn . ,args) ... ]
    [_ (raise-syntax-error
        'parse "not a valid CS450 Lang program" p
        #:exn exn:fail:syntax:cs450)]))
```

Programs that Add Variables to Environment

```
;; A Program is one of:  
;; - Atom  
;; - Variable (Var)  
;; - `(bind [,Var ,Program] ,Program)  
;; - ...
```

parse



```
;; An AST is one of:  
;; - ...  
;; - (mk-var Symbol)  
;; - (mk-bind Symbol AST AST)  
;; - ...
```

Need to be more careful parsing

Valid Program?

```
(check-exn exn:fail:syntax:cs450?  
  (λ () (eval450 '(bind))))
```

```
(check-exn exn:fail:syntax:cs450?  
  (λ () (eval450 '(bind []))))
```

```
(check-exn exn:fail:syntax:cs450?  
  (λ () (eval450 '(bind [1 2] 3)))))
```

```
;; ...  
;; (struct vari [name])  
;; (struct bind [var expr body])  
;; ...
```

Programs that Add Variables to Environment

```
;; A Program is one of:  
;; - Atom  
;; - Variable (Var)  
;; - `(bind [,Var ,Program] ,Program)  
;; - ...
```

parse



```
;; An AST is one of:  
;; - ...  
;; - (mk-var Symbol)  
;; - (mk-bind Symbol AST AST)  
;; - ...
```

```
;; ...  
(struct vari [name])  
(struct bind [var expr body])  
;; ...
```

run

???

Bind scoping examples

```
;; A Program is one of:  
;; - Atom  
;; - Variable (Var)  
;; - `(bind [,Var ,Program] ,Program)  
;; - ...
```

bind obeys “lexical” or “static” scoping

Generally accepted to be “best choice”
for programming language design
(bc it’s determined only by program syntax)

Var binding

Var reference


(check-equal?
(eval450 `(bind [x 10] x))
10) ; no shadow

(check-equal?
(eval450 `(bind [x 10]
 (bind [x 20]
 x))))
20) ; shadow

(check-equal?
(eval450
 `(bind [x 10]
 (+ (bind [x 20] x)
 x)))
30)

(check-equal?
(eval450
 `(bind [x 10]
 (bind [x (+ x 20)]
 x))))
30)

run, with bind



run, with bind

run must produce Result

;; run: AST -> Result

```
(define (run p)
  ;; accumulator env : Environment
  ;; invariant: contains in-scope var + results
  ; An AST is one of: env)
```

; - ...

; - (mk-bind Symbol AST AST)

```
[ (vari x) (env-lookup env x) ]
[ (bind x e body) ??? (env-add env x (run/env e env)) ... ]
  ...
  )
(run/env p ??? ))
```

run, with bind

```
;; run: AST -> Result
```

```
(define (run p)
  ;; accumulator env : Environment
  ;; invariant: contains in-scope var + results
  (define (run/env p env)
    (match p
      ...
      [(vari x) (env-lookup env x)]
      [(bind x e body) (run/env body (env-add env x (run/env e env)))]
      ...
    )
  (run/env p ??? ))
```

(From template!)

run body with new env containing x

Initial Environment?

```
;; run: AST -> Result
```

```
(define (run p)
  ;; accumulator env : Environment
  ;; invariant: contains in-scope var + results
  (define (run/env p env)
    (match p
      ...
      [(vari x) (env-lookup env x)]
      [(bind x e body) (run/env body (env-add env x (run/env e env)))]
      ...
    )
    (run/env p ??? ))
```

empty ??? (for now)

TODO:

- When are variables “added” to environment
- What is initial environment? `empty` (for now)

Initial Environment

```
;; A Program is one of:  
;; - Atom  
;; - Variable  
;; - `(bind [,Var ,Program] ,Program)  
;; - `(+ ,Program ,Program)  
;; - `(* ,Program ,Program)
```

These don't need to be separate constructs

Put these into “initial” environment

Initial Environment

```
;; A Program is one of:  
;; - Atom  
;; - Variable  
;; - `(bind [ ,Var ,Program] ,Program)  
;; - `(+ ,Program ,Program)  
;; - `(* ,Program ,Program)
```

Put these into “initial” environment

```
;; An Environment (Env) is one of:  
;; - empty  
;; - (cons (list Var Result) Env)
```

+ variable

```
(define INIT-ENV  
  `((+ ,450+)  
    (* ,450*)))
```

Maps to our “450+” function

New kind of Result

For Program: +

```
;; A Result is one of:  
;; - Number  
;; - UNDEFINED-ERROR  
;; - (Racket) Function
```

Initial Environment


How do users call these functions???

```
(define INIT-ENV '((+ ,450+) (* ,450*)))
```

```
(define (run p)
  ;; accumulator env : Environment
  (define (run/e p env)
    (match p
      ...
      [(vari x) (lookup env x)]
      [(bind x e body) (run/e body (env-add env x (run/e e env)))]
      ...
    )
    (run/e p INIT-ENV)
  ))
```

Function Application in CS450 Lang

```
;; A Program is one of:  
;; - Atom  
;; - Variable  
;; - `(bind [,Var ,Program] ,Program)  
;; - `(fncall ,Program . ,List<Program>)
```



Allows arbitrary number of args

Function Application in CS450 Lang: Examples

```
;; A Program is one of:  
;; - Atom  
;; - Variable  
;; - `(bind [,Var ,Program] ,Program)  
;; - `(fncall ,Program . ,List<Program>)
```

function

arguments

(**fncall** + 1 2)

Programmers shouldn't need to write the explicit "fncall"

Function Application in CS450 Lang: Examples

```
;; A Program is one of:  
;; - Atom  
;; - Variable  
;; - `(bind [,Var ,Program] ,Program)  
;; - `[,Program . ,List<Program>)
```

(+ 1 2)

Function Application in CS450 Lang: Examples

```
;; A Program is one of:  
;; - Atom  
;; - Variable  
;; - `(bind [ ,Var ,Program] ,Program)  
;; - `,(Program . ,List<Program>)  
;; - (cons Program List<Program>)
```

(+ 1 2)

Must be careful when parsing this

Function call case (must be last, why?)

Can go back to (simpler?) cons notation

(bind 1 2)

(should not be function call)

Function Application in CS450 Lang

```
;; A Program is one of:  
;; - Atom  
;; - Variable  
;; - `(bind [,Var ,Program] ,Program)  
;; - `[,Program . ,List<Program>]  
;; - (cons Program List<Program>)
```



;; An AST is one of:
;; - ...
;; - (mk-var Symbol)
;; - (mk-bind Symbol AST AST)
;; - (mk-call AST List<AST>)

(struct vari [name])
(struct bind [var expr body])
(struct call [fn args])

“Running” Function Calls

TEMPLATE: extract pieces of compound data

```
(define (run p)
  (define (run/e p env)
    (match p
      ...
      [(call fn args) (apply
                        (run/e fn env)
                        (map (curryr run/e env) args))])
      ...
    )))
(run/e p INIT-ENV))
```

;; An AST is one of:
;; - ...
;; - (mk-var Symbol)
;; - (mk-bind Symbol AST AST)
;; - (mk-call AST List<AST>)

(struct vari [name])
(struct bind [var expr body])
(struct call [fn args])

“Running” Function Calls

```
(define (run p)
```

;; An AST is one of:
;; - ...
;; - (mk-var Symbol)
;; - (mk-bind Symbol AST AST)
;; - (mk-call AST List<AST>)

```
(define (run/e p env)
```

```
  (match p
```

```
    ...
```

```
    [(call fn args) (apply
                      (run/e fn env)
                      (map (curry??? run/e env) args))]
```

```
    ...
  ))
```

```
(run/e p INIT-ENV))
```

TEMPLATE: recursive calls

“run” args before calling function – “call by value”

“Running” Function Calls

How do we actually run the function?

```
(define (run p)
```

```
(define (run/e p env)
```

```
  (match p
```

```
    ...
```

```
    [(call fn args) (apply  
                     (run/e fn env)  
                     (map (curryr run/e env) args))]
```

```
    ...
```

```
  ))
```

```
(run/e p INIT-ENV))
```

;; A Result is one of:
;; - Number
;; - UNDEFINED-ERROR
;; - (Racket) Function

Calls racket fns

Does this work???

“Running” Non-Functions

```
(define (run p)
```

;; A Result is one of:
;; - Number
;; - UNDEFINED-ERROR
;; - (Racket) Function

```
(define (run/e p env)
```

```
  (match p
```

```
    ...
```

```
    [(call fn args) (apply
```

```
      (run/e fn env)
```

```
      (map (curryr run/e env) args))]
```

```
    ...
```

```
  ))
```

```
(run/e p INIT-ENV))
```

Example:

```
(eval450 '(10 10)) ; apply non-fn
```

“Running” Non-Functions

```
(define (run p)
```

```
(define (run/e p env)
```

```
  (match p
```

```
    ...
```

```
    [(call fn args) (450apply  
                    (run/e fn env)  
                    (map (curryr run/e env) args))]
```

```
    ...
```

```
  ))
```

```
(run/e p INIT-ENV))
```

;; A Result is one of:
;; - Number
;; - UNDEFINED-ERROR
;; - NON-FUNCTION-ERROR
;; - (Racket) Function

Function application for CS450 Lang

;; A Result is one of:
;; - Number
;; - UNDEFINED-ERROR
;; - NON-FUNCTION-ERROR
;; - (Racket) Function

;; 450apply : Result Listof<Result> -> Result

```
(define (450apply fn args)
  (cond
    [(number? fn)           ... ]
    [(UNDEFINED-ERROR? fn)   ... ]
    [(NON-FUNCTION-ERROR? fn) ... ]
    [(procedure? fn)         ... ])))
```

TEMPLATE?

Function application for CS450 Lang

;; A Result is one of:
;; - Number
;; - UNDEFINED-ERROR
;; - NON-FUNCTION-ERROR
;; - (Racket) Function

;; 450apply : Result Listof<Result> -> Result

```
(define (450apply fn args)
  (cond
    [(number? fn) NON-FUNCTION-ERROR]
    [(UNDEFINED-ERROR? fn) ...]
    [(NON-FUNCTION-ERROR? fn) ...]
    [(procedure? fn) ...]))
```

Function application for CS450 Lang

;; A Result is one of:
;; - Number
;; - UNDEFINED-ERROR
;; - NON-FUNCTION-ERROR
;; - (Racket) Function

```
;; 450apply : Result Listof<Result> -> Result
```

```
(define (450apply fn args)
  (cond
    [(number? fn) NON-FUNCTION-ERROR]
    [(UNDEFINED-ERROR? fn) ...]
    [(NON-FUNCTION-ERROR? fn) ...]
    [(procedure? fn) (apply fn args)]))
```

Now this works

Function application for CS450 Lang

```
;; A Result is one of:  
;; - Number  
;; - UNDEFINED-ERROR  
;; - NON-FUNCTION-ERROR  
;; - (Racket) Function
```

```
;; 450apply : Result Listof<Result> -> Result
```

```
(define (450apply fn args)  
  (cond  
    [(number? fn) NON-FUNCTION-ERROR]  
    [(UNDEFINED-ERROR? fn) ... ]  
    [(NON-FUNCTION-ERROR? fn) NON-FUNCTION-ERROR]  
    [(procedure? fn) (apply fn args)])))
```

Function application for CS450 Lang

;; A Result is one of:
;; - Number
;; - UNDEFINED-ERROR
;; - NON-FUNCTION-ERROR
;; - (Racket) Function

```
;; 450apply : Result Listof<Result> -> Result
```

```
(define (450apply fn args)
  (cond
    [(number? fn) NON-FUNCTION-ERROR] UNDEFINED should have precedence over NON-FN-ERR
    [(UNDEFINED-ERROR? fn) UNDEFINED-ERROR]
    [(NON-FUNCTION-ERROR? fn) NON-FUNCTION-ERROR]
    [(procedure? fn) (apply fn args)]))
```

Function application for CS450 Lang

;; A Result is one of:
;; - Number
;; - UNDEFINED-ERROR
;; - NON-FUNCTION-ERROR
;; - (Racket) Function

Add ARITY-ERROR ???

;; 450apply : Result Listof<Result> -> Result

For now, we only use variable-arity functions

```
(define (450apply fn args)
  (cond
    [(UNDEFINED-ERROR? fn) UNDEFINED-ERROR]
    [(procedure? fn) (apply fn args)]
    [else NON-FUNCTION-ERROR]))
```

Combine cases

```
(define INIT-ENV
  `((+ ,450+)
    (* ,450*)))
```

Check correct number of arguments???

In-class Coding 4/22: bind + “call” examples

```
;; A Program is one of:  
;; - Atom  
;; - Variable  
;; - `(bind [,Var ,Program] ,Program)  
;; - `[,Program . ,List<Program>]
```

Come up with your own examples!

```
(check-equal?  
  (eval450 `(bind [x 10] x))  
  10 ) ; no shadow
```

```
(check-equal?  
  (eval450 `(bind [x 10] (bind [x 20] x))  
  20 ) ; shadow
```

```
(check-equal?  
  (eval450  
   `(bind [x 10]  
     (+ (bind [x 20]  
           x)  
     x)) ; 2nd x out of scope here  
  30 )
```

```
(check-equal?  
  (eval450  
   `(bind [x 10]  
     (bind [x (+ x 20)] ; x = 10 here  
           x))) ; x = 30 here  
  30 )
```